

JOYALL[®]
TIRES

JOYALL(WEIHAI) TIRE CO., LTD.

www.joyalltires.com



ALL STEEL RADIAL TRUCK TIRE

2024

JOYALL[®]
TIRES

PROFILE

42+

Years of Experience

150+

Countries& Regions

270,000+

m² Plant Area

100+

Sizes & Patterns

280+

Senior Engineers

Joyall (Weihai) Tire Co., Ltd founded in August 2010, with registered capital of RMB 130 million, is dedicated to the R&D, manufacturing and marketing of high performance TBR tires. It is solely invested by Shandong Joyall Technology Co., Ltd and located in the most livable city-Weihai, China, at Weihai International Port E&T Development Zone.

The first phase production line had been put into production in July 2015 with capacity up to 2.4 million sets of tires. The company's strategic goals are: to upgrade the version of China Tire industry on a sustainable development road, to make quality tires with cost performance and service advantage oriented, to be a national tire manufacturer of hundred years for a well-known brand in the world.



ROAD/POSITION



LONG-HAUL
05 - 28

STEER	DRIVE				DRIVE	TRAILER					
 A608+	 A702	 A705	 A878		 A888+	 A506	 A507	 A601	 A605	 A609	 A610
 A8	 A706	 A709	 B878			 A615	 A875	 A876	 A889	 B875	



REGIONAL
29 - 46

DRIVE					DRIVE	ALL			
 A802	 A803	 A805	 A807		 C958	 A9	 A505	 A509	 A515
 A812	 A815	 A958	 B958		 D909	 A919	 A959		



ON & OFF
47 - 52

ALL											
 A66+	 A903	 A928									



OFF
53 - 60

ALL				ALL							
 A906	 A907	 A908	 A913	 A916							



URBAN
61 - 66

ALL											
 A501	 A503	 A508									

LONG-HAUL

STEER	A608+ A8			
DRIVE	A702 A878	A705 A888+	A706 B878	A709
TRAILER	A605 A889 A601	A609 A507 A610	A875 A506 A615	A876 B875



A608+

Suitable for semi-trailer at steer position
Designed for long-distance standard load transportation
on highway or good paved road



Wear-Resistant

Uneven
Wear ResistanceScratch
Resistance**A8 A606**

Suitable for semi-trailer at trailer position
Designed for long-distance standard/overload
transportation on good paved road



Wear-Resistant

Uneven
Wear ResistanceScratch
Resistance

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
10.00R20	18	149/146	J	K	1054	272	16.5	3250	930	3000	930	7.5	-
11.00R20	18	152/149	J	K	1085	284	16.7	3550	930	3250	930	8.0	-
11R22.5	18	149/146	J	L	1054	270	16.5	3250	930	3000	930	8.25	-
12R22.5	18	152/149	J	L	1084	292	17.8	3550	930	3250	930	9.00	-
295/80R22.5	18	152/149	J	L	1045	292	16.8	3550	900	3250	900	9.00	-
215/75R17.5	16	135/133	H	L	766	212	13.5	2180	850	2060	850	6.00	-
315/80R22.5	20	157/154	L	K	1076	310	16.5	4125	900	3750	900	9.00	-

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11R22.5	16	146/143	H	L	1050	272	16.5	3000	830	2725	830	8.25	-
12R22.5	18	152/149	J	L	1081	293	16.5	3550	930	3250	930	9.00	-
295/80R22.5	18	152/149	J	M	1042	295	16.8	3550	900	3250	900	9.00	-
315/80R22.5	20	157/154	L	L	1076	316	16.5	4125	900	3750	900	9.00	-

A702



Suitable for semi-trailer at drive position
Designed for long-distance overload transportation on
highway or good paved road



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
315/70R22.5	18	151/148	J	L	1020	310	23.0	3450	830	3150	830	9.00	M+S
315/80R22.5	20	157/154	L	K	1090	316	21.8	4125	900	3750	900	9.00	M+S

A705



Suitable for semi-trailer at drive position
Designed for long-distance overload transportation on
highway or good paved road



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
235/75R17.5	18	143/141	J	L	-	-	14.0	2725	900	2575	900	6.75	-
295/80R22.5	18	152/149	J	L	1053	290	18.8	3550	900	3250	900	9.00	-



A706



Suitable for semi-trailer at drive position
Designed for long-distance overload transportation on
highway or good paved road



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12R22.5	18	152/149	J	L	1092	290	18.8	3550	930	3250	930	9.00	M+S



A709



Suitable for semi-trailer at drive position
Designed for long-distance overload transportation on
highway or good paved road



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
295/80R22.5	22	160/157	-	K	1072	-	21	4500	900	3250	900	9	-

A878

Suitable for semi-trailer at drive position
Designed for long-distance overload transportation on
highway or good paved road



Powerful
Braking



Self-
Cleaning

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
285/75R24.5	16	147/144	H	L	1059	272	21.5	3075	830	2800	830	8.25	-
295/75R22.5	16	146/143	H	L	1020	288	22.0	3000	830	2725	830	9.00	-
11R22.5	16	146/143	H	L	1061	272	22.0	3000	830	2725	830	8.25	-
11R24.5	16	149/146	H	L	1106	268	21.5	3250	830	3000	830	8.25	-

A888+

Suitable for drive position of dumper and semi-trailer
Designed for mid-long distance standard load
transportation on paved road at high speed



Powerful
Braking



Wear-
Resistant

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
315/80R22.5	20	157/154	L	K	1080	316	24.0	4125	900	3750	900	9.00	M+S

JOYALL[®]
TIRES

B878 G201



Suitable for semi-trailer at drive position
Designed for long-distance overload transportation on
highway or good paved road



Wear-
Resistant



Powerful
Braking



Self-
Cleaning

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11R22.5	16	146/143	H	L	1061	272	22.0	3000	830	2725	830	8.25	M+S
12R22.5	18	152/149	J	L	1086	290	22.0	3550	930	3250	930	9.00	M+S
295/80R22.5	18	152/149	J	M	1053	295	22.0	3550	900	3250	900	9.00	M+S
315/80R22.5	20	157/154	L	L	1081	312	22.0	4125	900	3750	900	9.00	M+S

LONG-HAUL



A506

Suitable for semi-trailer at all position
Designed for long-distance overload transportation on
highway or good paved road

Wear-
ResistantPowerful
Braking

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12R22.5	18	152/149	J	L	1082	290	17.5	3550	930	3250	930	9.00	-

A507

Suitable for semi-trailer at trailer position
Designed for longdistance overload transportation
on highway or good paved road

Wear-
ResistantSelf-
Cleaning

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12R22.5	18	152/149	J	L	1080	290	15.3	3550	930	3250	930	9.00	-



A601



Suitable for steer & trailer positions
Designed for mid&long distance overload transportation
on paved road at mid speed



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
385/65R22.5	24	164	N	J	1073.4	386	16.5	5000	900	-	-	11.75	-



LONG-HAUL



A605



Suitable for semi-trailer at all position
Designed for long-distance standard load transportation
on highway or good paved road



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
7.00R16LT	14	118/114	G	N	775	198	12.4	1320	1180	5.50F	-	-	-
7.50R16LT	16	125/121	H	L	806	210	13.5	1650	870	1450	870	6.00G	-
8.25R16LT	18	132/128	J	L	860	230	15.0	2000	870	1800	870	6.50H	-
12R22.5	18	152/149	J	L	1082	290	17.0	3550	930	3250	930	9.00	-
235/75R17.5	18	143/141	J	J	802	234	13.2	2725	875	2575	875	6.75	-
245/70R19.5	18	142/140	J	K	841	246	14.3	2650	900	2500	900	7.50	-
275/70R22.5	18	152/149	J	J	962	280	15.5	3550	900	3250	900	8.25	-
275/80R22.5	18	149/146	J	L	1015	280	16.5	3250	900	3000	900	8.25	-
295/60R22.5	18	150/147	J	L	926	292	17.3	3350	900	3075	900	9.00	-

A609



Suitable for semi-trailer at trailer position
Designed for long-distance standard load transportation
on highway or good paved road



Wear-
Resistant



Uneven
Wear Resistance



Anti-
Skidding



A610



Suitable for trailer positions
Designed for regional mid&short distance overload
transportation on paved road at mid speed



Wear-
Resistant



Self-
Cleaning



Anti-
Skidding



Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12R22.5	18	152/149	J	L	1080	290	15.3	3550	930	3250	900	9.00	-

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
385/65R22.5	24	164	N	J	1071.4	386	16.0	5000	900	-	-	11.75	-
385/55R22.5	20	160	L	K	996	380	15.0	4500	900	-	-	12.25	-

A615

Suitable for trailer positions
Designed for regional mid&short distance overload
transportation on paved road at mid speed



Wear-Resistant



Self-Cleaning



Anti-Skidding

Uneven
Wear Resistance

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
385/65R22.5	24	164	N	J	1073	382	15.5	5000	900	-	-	11.75	-

A875

Suitable for semi-trailer at trailer position
Designed for long-distance standard load transportation
on highway or good paved road



Wear-Resistant

Uneven
Wear Resistance

Anti-Skidding

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11R22.5	16	146/143	H	L	1039	272	11.0	3000	830	2725	830	8.25	-
12R22.5	18	152/149	J	L	1074	290	15.2	3550	930	3250	930	9.00	-
295/75R22.5	16	146/143	H	L	998	288	11.0	3000	830	2725	830	9.00	-

A889

Suitable for semi-trailer at trailer position
Designed for long-distance overload transportation on
highway or good paved road



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12R22.5	18	152/149	J	L	1075	290	16.5	3550	930	3250	930	9.00	-
13R22.5	20	156/153	L	-	1115	308	16.5	4000	930	3650	930	9.75	-

**A876 G102**

Suitable for semi-trailer at trailer position
Designed for long-distance standard/overload
transportation on good paved road



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11R22.5	16	146/143	H	L	1047	272	15.0	3000	830	2725	830	8.25	-
11R24.5	16	149/146	H	L	1093	268	14.8	3250	830	3000	830	8.25	-
12R22.5	18	152/149	J	L	1074	290	16.2	3550	930	3250	930	9.00	-
285/75R24.5	16	147/144	H	L	1046	272	14.5	3075	830	2800	830	8.25	-
295/75R22.5	16	146/143	H	L	1006	288	15.0	3000	830	2725	830	9.00	-
295/80R22.5	18	152/149	J	M	1039	295	15.0	3550	900	3250	900	9.00	-
315/80R22.5	20	157/154	L	L	1076	310	15.0	4125	900	3750	900	9.00	-

B875



Suitable for semi-trailer at trailer position
Designed for long-distance overload transportation on
highway or good paved road



Low Heat
Buildup



Uneven
Wear Resistance

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
7.50R16LT	16	125/121	H	L	803	212	12.4	1650	870	1450	870	6.00G	-
12.00R24	20	160/157	L	K	1226	304	17.0	4500	900	4125	900	8.5	-
11R22.5	16	146/143	H	L	1047	272	15.0	3000	830	2725	830	8.25	-
12R22.5	18	152/149	J	L	1074	290	15.0	3550	930	3250	930	9.00	-
315/80R22.5	20	157/154	L	L	1076	310	16.0	4125	900	3750	900	9.00	-



REGIONAL

DRIVE	A802	A803	A805	A807	A812	
	A815	A958	B958	C958	D909	
ALL	A9	A505	A509	A515	A919	A959



A802

Suitable for drive position of trailer and dumper
Designed for mid-short distance heavy load transportation
on mixed road conditions at mid-low speed



Wear-Resistant



Long-Lasting

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
315/80R22.5	20	157/154	L	D	1080	316	22.0	4125	900	3750	900	9.00	-

A803

Suitable for rear axle of dump truck
Designed for mid-short distance standard load transportation
on mixed road conditions at mid-low speed



Anti-puncture



Self-Cleaning

Uneven
Wear Resistance

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12R22.5	18	152/149	J	K	1094	293	23.0	3550	930	3250	930	9.00	M+S

A805



Suitable for semi-trailer at drive position
Specially engineered for the toughest road conditions &
extra-heavy load



Wear-
Resistant



Self-
Cleaning

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11R22.5	16	148/145	H	K	1062	276	23.0	3150	850	2900	850	8.25	-

A807



Suitable for drive position of dumper and semi-trailer
Designed for mid-short distance heavy load transportation
on mixed road conditions at mid-low speed



Long-
Lasting



Self-
Cleaning



Powerful
Braking

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12.00R24	20	160/157	L	K	1229	308	19.5	4500	900	4125	900	8.5	-



A815



Suitable for drive position of drive at dumper
Designed for mid-short distance heavy load transportation
on mixed road conditions at mid-low speed



Low Heat
Buildup



Long-
Lasting

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12.00R20	22	158/155	M	G	1125	304	21.3	4250	970	3875	970	8.5	-
13R22.5	22	158/156	M	G	1125	305	21.3	4250	900	4000	900	9.75	-
12R22.5	18	-	J	k	-	K	20	3550	930	3250	930	9.00	-



A812 A808



Suitable for drive position of dumper
Designed for short distance heavy load transportation
on mixed road conditions at low speed



Low Heat
Buildup



Long-
Lasting



Grip

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12.00R20	22	156/153	L	K	1125	304	18.8	4000	900	3650	900	8.5	-
13R22.5	22	158/156	M	G	1125	305	20.3	4250	900	4000	900	9.75	-
315/80R22.5	20	157/154	L	K	1076	316	23.0	4125	900	3750	900	9.00	-



A958



Suitable for drive position of dumper and semi-trailer
Designed for mid-short distance heavy load transportation
on mixed road conditions at mid-low speed



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
10.00R20	18	149/146	J	K	1058	278	18.0	3250	930	3000	930	7.5	-
11.00R20	18	152/149	J	K	1085	286	19.0	3550	930	3250	930	8.0	-
12.00R20	22	156/153	L	K	1124	310	19.0	4000	900	3650	900	8.5	-
12R22.5	18	152/149	J	K	1085	293	19.0	3550	930	3250	930	9.00	-
13R22.5	22	158/156	M	G	1124	316	19.0	4250	900	4000	900	9.75	-



REGIONAL



B958



Suitable for drive position of dumper
Designed for short distance heavy load transportation
on mixed road conditions at low speed



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
10.00R20	18	149/146	J	J	1064	278	21.8	3250	930	3000	930	7.5	-
11.00R20	18	152/149	J	J	1080	286	21.0	3550	930	3250	930	8.0	-
12.00R20	20	156/153	L	J	1121	310	22.0	4000	900	3650	900	8.5	-

C958

Suitable for drive position of dumper and semi-trailer
Designed for short distance transportation on mixed road
conditions at mid-low speed



Powerful
Braking

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11.00R20	18	152/149	-	K	1080	284	18.5	3550	930	3250	930	8.00	-
12.00R20	18	154/151	-	K	1115	308	18.6	3750	830	3450	830	8.50	-
12.00R20	20	156/153	-	K	1115	308	18.6	4000	900	3650	900	8.50	-
12R22.5	18	152/149	-	K	1080	290	18.5	3550	930	3250	930	9.00	-

**D909**

Suitable for drive position of dumper and semi-trailer
Designed for mid-short distance heavy load transportation
on mixed road conditions at mid-low speed



Low Heat
Buildup



High
Load



Grip

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11.00R20	18	152/149	J	K	1080	284	18.5	3550	930	3250	930	8.0	-
12.00R20	20	156/153	L	K	1119	308	20.6	4000	900	3650	900	8.5	-

A9

Suitable for dump truck and semi-trailer at all positions
Designed for mid-short distance heavy load transportation
on paved road at mid-low speed



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
10.00R20	18	149/146	J	K	1054	278	16.0	3250	930	3000	930	7.5	-
11.00R20	18	152/149	J	K	1080	286	16.5	3550	930	3250	930	8.0	-
12.00R20	22	156/153	L	K	1120	310	17.0	4000	900	3650	900	8.5	-
11R22.5	18	149/146	J	L	1054	272	16.0	3250	930	3000	930	8.25	-
13R22.5	20	156/153	L	K	1120	316	17.0	4000	930	3650	930	9.75	-

A505

Suitable for trailer and dumper at all positions
Designed for mid&short distance overload transportation
on paved road at mid-low speed



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12.00R24	20	160/157	L	K	1226	308	16.0	4500	900	4125	900	8.5	-

A515

Suitable for dump truck and semi-trailer at all positions
Designed for mid-short distance heavy load transportation
on paved road at mid speed



Anti-puncture



Self-Cleaning

Uneven
Wear Resistance

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
7.50R16LT	16	125/121	H	L	806	210	14.0	1650	870	1450	870	6.00G	-
8.25R16LT	18	132/128	J	L	860	230	15.0	2000	870	1800	870	6.50H	-

A509

Suitable for semi-trailer at all position
Designed for regional medium distance overload
transportation on good paved road



Wear-Resistant



Self-Cleaning



Long-Lasting

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12R22.5	18	152/149	J	L	1085	290	18.0	3550	930	3250	930	9.00	-

A959

Suitable for all positions
Designed for mid&short distance standard load transportation
on paved road at mid-low speed



Low Heat
Buildup



Self-
Cleaning



High
Load

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11.00R20	18	152/149	J	K	1078	282	15.0	3550	930	3250	930	8.0	-

**A919**

Suitable for semi-trailer at all positions
Designed for mid-short distance overload transportation
on paved road at mid speed



Anti-
Skidding



Wear-
Resistant



Powerful
Braking

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12R22.5	18	152/149	J	L	1081	293	16.5	3550	930	3250	930	9.00	-

ON & OFF

ALL A66+ A903 A928





Suitable for drive positions of dumper
Designed for short distance heavy load transportation
on mixed road at low speed



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
9.00R20	16	144/142	H	D	1032	260	24.5	2800	900	2650	900	7.0	-
10.00R20	18	149/146	J	D	1068	278	24.5	3250	930	3000	930	7.5	-
11.00R20	18	152/149	J	D	1088	286	25.0	3550	930	3250	930	8.0	-
12.00R20	20	156/153	L	D	1130	310	24.0	4000	900	3650	900	8.5	-



ON & OFF



A903



Suitable for drive positions of dumper
Designed for short distance heavy load transportation
on rough roads at mid low speed



Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
295/80R22.5	20	154/150	L	D	1052	295	21.0	3750	850	3350	850	9.00	-

A928

Suitable for drive position of dumper
Designed for mid-short distance standard load transportation
on mixed road at mid speed



Powerful
Braking

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12.00R24	20	160/157	L	K	1240	308	25.0	4750	970	4375	970	8.5	-
12R22.5	18	152/149	J	K	1096	293	24.0	3550	930	3250	930	9.00	-
295/80R22.5	20	154/150	L	J	1050	295	21.0	3750	850	3350	850	9.00	-
315/80R22.5	22	161/157	-	D	-	-	24.0	-	-	-	-	-	-

OFF

ALL

**A906 A907 A908 A913
A916**



A906

Suitable for drive positions of dumper
Designed for short distance heavy load transportation
on rough roads at low speed

Wear-
ResistantLow Heat
BuildupScratch
Resistance

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11.00R20	20	153/150	L	D	1102	282	24.0	3650	970	3350	970	8.0	-
12.00R20	20	156/153	L	D	1134	304	24.0	4000	900	3650	900	8.5	-
12R22.5	18	152/149	J	F	1102	290	24.0	3550	930	3250	930	9.00	-
13R22.5	22	158/156	M	D	1134	307	24.0	4250	900	4000	900	9.75	-

A907 A915

Suitable for drive positions of dumper
Designed for short distance overload mining transportation
on bad gravel roads at low speed

Scratch
ResistanceLong-
Lasting

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11.00R20	20	153/150	L	D	1102	280	28.0	3650	970	3350	970	8.0	-
12.00R20	20	156/153	L	D	1134	302	26.0	4000	900	3650	900	8.5	-

A908

Suitable for drive positions of dumper
Designed for short distance heavy load mining transportation
on unpaved road



Low Heat
Buildup



Self-
Cleaning



High
Load

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11.00R20	20	153/150	L	D	1102	282	26.0	3650	970	3350	970	8.0	-
12.00R20	20	156/153	L	D	1136	302	24.8	4000	900	3650	900	8.5	-
12R22.5	18	152/149	J	F	1102	290	26.0	3550	930	3250	930	9.00	-

A913

Suitable for drive positions of dumper
Designed for short distance heavy load transportation on
mixed road at low speed



Long-
Lasting



Anti-
puncture



Uneven
Wear Resistance



Powerful
Braking

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12.00R20	20	156/153	L	B	1147	306	33.5	4000	900	3650	900	8.5	-



A916



Suitable for all positions of dumper
Designed for short distance heavy load transportation on
rough roads at low speed



Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12.00R20	20	156/153	L	D	1134	306	23.7	4000	900	3650	900	8.5	-



URBAN

ALL A501 A503 A508





A501



Suitable for all position of bus
Designed for Urban and intercity short distance transport on paved road at mid speed



Wear-Resistant



Powerful Braking

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
12R22.5	18	152/149	J	L	1092	305	21.5	3550	930	3250	930	9.00	-
11R22.5	16	148/145	H	J	1060	282	22.0	3150	850	2900	850	8.25	-
275/70R22.5	18	152/149	J	J	962	280	22.5	3550	900	3250	900	8.25	-



A503



Suitable for all position of bus
Designed for Urban and intercity short distance transport on paved road at mid speed



Self-Cleaning



High Load



Anti-Skidding

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11R22.5	16	148/145	H	J	1060	282	22.0	3150	850	2900	850	8.25	-
275/70R22.5	18	150/145	J	J	962	280	22.0	3350	900	2900	900	8.25	-
295/80R22.5	18	152/149	J	K	1051	292	21.0	3550	900	3250	900	9.00	-

A508



Suitable for all position of bus
Designed for Urban and intercity short distance transport on paved road at mid speed



Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim	M+S
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)		
11R22.5	16	148/145	H	J	1060	282	22.0	3150	850	2900	850	8.25	-

